



# Floor Scarifier



# Floor Scarifier

Outstanding Performance in Floor Milling and Coating Removal.



### 株式会社 ライナックズ

本 社 〒359-0027 埼玉県所沢市松郷151-6

T 04-2946 5211

W www.linax.co.jp

F 04-2946 5212

(e) linax@linax.net

LINAX co., LTD.

Head Office: 151-6 Matsugo, Tokorozawa-shi, Saitama-ken, 359-0027 Japan.


T 81-4-2946 5211

W www.linax.co.jp

F 81-4-2946 5212

(e) linax@linax.net





# Scarifiers series

- Handheld Scarifier
- Compact Scarifier
- Heavy-duty Scarifier

High quality, strong and robust scarifying machines. These machines have a very effective working performance and are available in 50mm, 200mm and 220mm working width for small to large sized areas.

Available in a range of engine and electric powered models suitable for light to heavy duty work.

Specially designed with high quality cutter tools, for effective floor milling and coating removal.

Connectable with a dust collector to greatly improve the working environment.



	<b>HF-50E</b> Powerful Chipper	FC-200 II Chopper II (Gasoline)	FC-200E II Chopper II (Electric)	F-22 Heavy-Duty (Gasoline)	F-22E Heavy-Duty (Electric)
LxWxH(mm)	537 × 180 × 235	993 × 506 × 1066	1041 × 506 × 1066	1020∼1600 x 525 x 950	1020 <b>~</b> 1600 × 525 × 925
Total Weight (kg)	3.0 w/o Cutters (7.5 w/Cutters)	111.5	100.5	200 (Incl. Counter Weight 30)	220 (Incl. Counter Weight 30)
Working Width (mm)	50	200		225 ~ 229	
Working Depth (mm)	Adjustable up to 5	Adjustable up to 5		Stepless Adjustment	
Edge Remainder (mm)	12	60		44	
Cutter Rotation	Down Cut	Down Cut		Down Cut	
Output (kW)	1.2kW	Honda GX270 5.6kW	3.7kW x 4P	8.1kW	5.5kW x 4P
Power	220V	Unleaded Gasoline	380/415 V (50/60Hz)	Unleaded Gasoline	380/415 V (50/60Hz)
Dust Collector (Optional)	L-1 / V-1 / V-2	V-2 (220/240V) Connect with an optional suction hose (50mm x 7m)		V-2 (220/240V) Couple behind the machine.	



# **HF-50E**

### **Powerful Chipper**

#### **Standard Accessories**

- Cutter Drum w/SP Cutters
- Dust Collection Hose (38mm x 4m)
- Drum Installation Tool
- Allen Wrenches (4mm & 6mm)



#### **Optional Accessories**

SP Cutters (Tungsten Carbide) w/Spacers and Shafts Set Includes: SP Cutters, 30pcs Cutter Spacers, 36pcs Cutter Shafts, 6pcs

\*\*\*Spare cutters, spacers and shafts can be purchased separately.\*\*\*



## Features

LINAX "POWERFUL CHIPPER" provides outstanding performance when working on vertical surfaces, edges, and hard-to-reach areas.

Connectable with a dust collection hose with a fully enclosed metal cover to maintain a clean working environment.

Working depth can be adjusted using a sliding system.





Remove thin to medium coating up to 2mm.



Works on concrete surfaces at the edges, and hard to reach areas.



Works on walls or ceilings.

4-or 6-Shaft-Cutter Setup.




4-Shaft-Cutter Setup (20pcs cutters)



6-Shaft-Cutter Setup (30pcs cutters)

#### **Surface Profile**

On concrete surface.



4-shaft-cutter setup: Creates rougher surface for medium to thick coating.6-shaft-cutter setup: Creates smoother surface for thin to medium coating.

On 2mm epoxy coating.

6-shaft

4-shaft

#### SP Cutters

OD: 35mm x ID: 12mm x Width: 6mm High quality tungsten carbide cutters.

Application:

Removal of coatings or paints, on vertical and horizontal surfaces.

Working depth up to 5mm per pass.



■ Adjustable running speed 600~3000rpm.



Adjustable working depth up to 5mm using a sliding system.



# FC-200/E II

### **Chopper II**

#### **Standard Accessories**

- Cutter Drum w/6PT Cutters
- Extra Cutter Spacers, 6pcs
- Drum Retaining Tool
- Single Ring Spanner (30mm)
- Ring Spanner (10 x 12 mm)
- Open-ended Spanner (17 x 19 mm)



#### **Optional Accessories**

6PT Cutters (Tungsten Carbide) w/Spacers and Shafts Set Includes: 6PT Cutters, 102pcs Cutter Spacers, 114pcs

Cutter Shafts, 6pcs

\*\*\*Spare cutters, spacers and shafts can be purchased separately.\*\*\*



### Features

- The FC-200 series
   walk-behind scarifiers feature a
   200mm working width with a
   rigid and compact design.
- These very well-built machines provide low vibration, are well-balanced during operation and perform excellent surface profiles.
- Specially designed with high quality, long life tungsten carbide cutters, with a side loading drum for quick and easy cutter replacement.
- Designed to be used with LINAX Dust Collectors.



**Gasoline & Electric Models Available.** 







Easy to use depth adjusting handwheel.




Brake system to control forward speed.



 Vibration absorbtion handle.



Easy side loading drum with sliding system.



■ 6PT Cutters

OD: 57mm x ID: 17.5mm x Width: 6mm High quality tungsten carbide cutters.

Application:

Removal of coatings and paint on concrete surfaces and asphalt.
Working Depth up to 5mm per pass.



 Cable hook to avoid running over or damaging cable.



 Equipped with motor direction control switch.



## F-22/E

### **HEAVY DUTY**

#### **Standard Accessories**

- Tool Box
- Cable Hanger
- 22-2V Joint Plate
- Standard Collars (113mm) 6pcs
- Short Collars (109mm) 2pcs
- Portable Earth Leakage Breaker









### Features

- Built from the heaviest and most durable materials producing very efficient scarifiers.
- By using the centrifugal force of cutters to produce a powerful force, the machines work efficiently on roughening the concrete and removing hard and thick coatings.





- Specially designed with 3 different cutters suitable for surface preparation, scarification and milling application.
- LINAX dust collectors can be coupled behind the scarifier to create dustless operation and easy handling by one person without assistance.



Brake system to control forward speed.




Equipped with a motor direction control switch.



### **Attachable with Dust Collector**

Keep your jobsite clean and environmentally friendly.

Model V-2 (220V/240)



Features an adjustable handle to fix your working position and make for easy storage.





# **F-22/E**

## **Features**

An additional counterweight (30kgs) is loaded on top of the drum to create extra downward pressure which is useful when working on heavy-duty jobs. It can also be unloaded easily for transportation.



Easy working depth adjuster.



Cable hanger to avoid running over or damaging cable.



Removal of 10mm resin mortar MMA (methyl-methacrylate).



■ Removal of epoxy coating 2~4mm.



■ The scarifier can be operated individually by connecting the dust collector separately.



### **SELECTION OF F-22/E CUTTERS**

### **Cutters Removal Depth** 1-2 **Pointed** Steel Removal Depth: 1 - 2mm

Service Life: Short (10hrs/set)



**Surface Profile** 

30 PT Steel Cutter 204 Cutters & 6 Shafts per set

Model F-22/E

#### **Description**

- Roughening of concrete surfaces or anti-slip surface preparation.
- Removing frost damaged surfaces or residues of adhesives after floor coverings are removed.
- Removing traffic/airport paint lines and thin coatings.





Removal Depth: 2-4mm Service Life: Longest (150hrs/set)





8PT Tungsten Carbide 84 Cutters & 6 Shafts per set



Scarifying hard to normal concrete.

Milling application.


marks.

Removing epoxy mortar,

thin coatings, and fragile

surfaces with raindrop





Removal Depth: 7 - 10mm



Service Life: Long (100hrs/set)










6 Edge Carbide Miller 30 Cutters & 6 Shafts per set



<sup>\*\*\*</sup>Spare cutters, spacers and shafts can be purchased separately.\*\*\*

<sup>\*\*</sup>The above technical data is subject to change, depending on different materials, concrete